

## New Product Announcement January 2020

## 675 smartVAC2

The **Model 675 SmartVAC2** is designed for general purpose sealing applications where reliability and flexibility are paramount to your operation. This time-controlled sealer offers an affordable sealing solution for a multitude of applications. The impulse heating technology employed in the Model 675 SmartVAC2 allows for sealing of virtually all bag or pouch materials, with the added features of vacuum and gas purging if required.

## **Features/Improvements**

- High Resolution Color-Enhanced Display
  - Ease of set-up and operation.
- Multiple Seal Lengths
  - O Available in 20, 25 or 30-inch seal lengths.
  - 1/4" seal width (std); 3/8" available
- > Improved Safety and Reliability
  - o Dual, independent jaw obstruction sensing and alarms.
  - DC control circuit.
  - Display remains powered with E-Stop engaged.
- > Recipe and Password Protection (Optional)
  - o Up to 10 recipe settings
  - Multi-level password protection to parameter/alarm settings.
- ➤ High Flow Nozzle/Ejector Option
  - Fast evacuation for vacuum sealing larger bags.
- > Available in 2 Configurations
  - o 675V2 Vacuum-Seal
  - o 675M2 Gas-Vacuum-Seal
- Powder Coated Welded Stainless-Steel Case



